

COMPOSITES

Datasheet Finishmat® 6691

Lantor Finishmat® 6691

- Chemical and weather resistance
- Smooth surface
- Available in a white and a grey color
- Controlled resin drainage
- Prevention of fibre print through
- High abrasive resistance
- Easy to process due to high tensile strength
- Good resin retention
- Compatible with thermoset resins
- Excellent resin wet-out

Applications Lantor Finishmat® 6691

- Industrial: pipes, containers, tanks, profiles and rods
- General Pultrusion and Filament Winding applications

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provide at any time without further notice.

Dimensional data

Properties		6691 SL	6691 LL
Thickness	mm	0,30	0,45
Roll length	m	1000	1000
Roll width	m	1,0	1,0
Resin uptake	kg/m ²	0,35	0,50
Dry weight	g/m ²	20	40
Binder type		Acrylate	Acrylate
Elongation	%	>10	>10
Fibre type		Polyester	Polyester

Information

PO box 45 - 3900 AA
Verlaat 22 - 3901 RG
Veenendaal
The Netherlands
T +31(0) 318 537 111
composites@lantor.com

enabling performance
www.lantor.com

