

COMPOSITES

Datasheet Finishmat® D77



Lantor Finishmat® D77

- Excellent surface finish
- Reduction of process cycle time
- Gelcoat can be replaced by pigmented resin
- Easy to process
- Becomes translucent in resin
- High elongation

Applications Lantor Finishmat® D77

- Marine: hulls, decks, and structures of boats and yachts
- Transportation: parts and panels of cars, trailers, trucks and RV's
- General closed mould applications

Dimensional data

Properties		D77 60	D77 80
Thickness*	mm	0,30	0,40
Roll length	m	100	100
Roll width	m	Several widths	Several widths
Resin uptake*	kg/m ²	0,40	0,55
Dry weight	g/m ²	60	80
Binder		Needle punched	Needle punched
Elongation	%	100	100
Fibre type		PAN	PAN
* depending on process pressure			

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provide at any time without further notice.

Information

PO box 45 - 3900 AA
Verlaat 22 - 3901 RG
Veenendaal
The Netherlands
T +31(0) 318 537 111
composites@lantor.com

enabling performance
www.lantor.com

